

DGPR 20 ST

RentalPlus Range



Ideal for...



Weight with liquids without fuel: 700 kg

Dimensions
Plat AK:
L: 1875 mm
W: 962 mm
H: 1215 mm




Image for orientation purposes. Dagartech reserves the right to modify the data in this technical sheet without prior notice. The weight of the equipment may vary depending on the equipment.



1. General technical data

General technical data	Engine	PERKINS 404J-22
	Alternator	STAMFORD S0L2-G
	Type of execution	G2
	Frequency	50Hz
	Voltage	400/230V
	Control panel	DSE 3110
	Fuel tank (l)	105
	Sound level-Lp(A) (dB(A)@7m)	61
Sound power-LW(A) (dB(A))	89	

Power¹ (m.p. cos φ 0,8)	PRP (kVA / kW)	20 / 16
	ESP (kVA / kW)	22 / 18

¹PRP: Continuous power ("Prime Power"). ESP: Emergency Standby Power according to ISO8528-1.
Maximum active power tolerance (kW) ±5%

Voltage	PRP (KVA/KW)	ESP (KVA/KW)	Amperage (A)
400/230V	20 / 16	22 / 18	32

Directives and Regulations

ENVIRONMENTAL CONDITIONS STANDARD ISO 8528-1:2018: 25°C, 100kPa and 30% relative humidity:

- **Prime Power (PRP):** Data on electrical power available at variable load without limit of hours per year. An overload of 10% is allowed for 1h out of 12. According to ISO 8528-1:2018.
- **Emergency Standby Power (ESP):** Data on electrical capacity available at variable load in case of emergency according to ISO 8528-1:2018.

The DAGARTECH Generating Set has EC labelling which includes the following directives:

- **2006/42/EC.** Machine Safety Directive.
- **EN ISO 8528-13:2016. Part 13: Safety.** Alternating current generator sets powered by reciprocating internal combustion engines.
- **2014/30/EU. Electromagnetic Compatibility Directive.**
- **2000/14/EC. Noise Emissions Directive.** Sound power levels evaluated in accordance with the procedure laid down in the directive.
- **Directive 2011/65/EU** on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS 2).

2. Engine specifications

2.1. General technical data of the engine	Make and model	PERKINS 404J-22			
	r.p.m.	1500			
	Maximum ESP power (kWm)	20,5			
	Power PRP (kWm)	18,5			
	Fuel	Diesel			
	No. of cylinders	4 cylinders			
	Cylinder capacity (c.c.)	2220			
	Compression ratio	23,3:1			
	Cooling system	Water cooled			
	Type of regulation	mechanical			
Type of engine/injection/suction	Diesel/Consult/natural				
2.2. Fuel	Type of fuel	Diesel			
	Fuel tank capacity	105			
2.3. Consumption and autonomy	Consumption (l/h)		Autonomy (h)		
		PRP	ESP	PRP	ESP
	50%	2,9	-	36,1	-
	75%	4	-	26,2	-
	100%	5,5	6,3	19	16,7
2.4. Cooling system	Fan flow (m ³ /s)	1			
	Fan power consumption (kW)	0,1			
	Radiator back pressure (Pa)	80			
	Total refrigerant capacity (l)	7			
2.5. Lubrication system	Oil capacity (l)	6			
2.6. Intake system	Combustion air intake flow (m ³ /min)	2			
2.7. Starter system	No. of batteries	1			
	Battery characteristics	12V 60Ah			
	Start-up voltage (V)	12V			
2.8. Exhaust system	Exhaust gas flow (m ³ /min)	3,64 [PRP]	3,94 [ESP]		
	Exhaust gas temperature (°C)	490° [PRP]	490° [ESP]		
	Exhaust outside diameter (mm)	2" - Ø50mm			
	Max. exhaust back pressure (kPa)	10			

- **4 cylinders 4-stroke diesel engine online** with mechanical regulation mechanical by means of a fuel pump, original from the manufacturer.



Emissions compliance
EU Stage V

- **Direct injection and suction system natural.** Original manufacturer's particle separator filter.

- **Refrigeration through cooling liquid,** fully distributed in the closed circuit run by an engine driven pump, tropicalised radiator, original from the engine manufacturer.

- **Crankshaft-driven pump lubrication system.** The filter is a full-flow insert cartridge, front housing, original from the engine manufacturer.

- **Air intake system for turbo-fed combustion** with two-stage filter, original from the engine manufacturer.

- **Electric motor starting system, battery** (no maintenance) **with disconnecter and load alternator driven by the starter** 12V, original elements from the engine manufacturer.

Exhaust attenuation level
-30dB(A)

3. Alternator specifications

3.1. General technical data for the alternator

Make and model	STAMFORD S0L2-G			
No. of poles	4			
Insulation class	H			
No. of threads	12			
Mechanical protection index	IP23			
Voltage Regulator (AVR)	AS540			
Voltage regulation	±1%			
ESP power 27°C (kVA)	22			
Power PRP 40°C (kVA)	20			
No. of phases	3			
Power factor (cos φ)	0,8			
Performance η (%)				
	50%	75%	100%	110%
	89,0%	87,9%	85,3%	83,8%

- **Brushless 4-pole alternator.** Robust mechanical structure with easy access to connections and components. Insulation class H, coil pitch 2/3 and self-excited AVR.
- **Protection with premium epoxy resins.** High voltage parts are impregnated under vacuum, which always means very good insulation.

Standard regulations that the alternator fulfils:

AS 1359 | IEC 34-1 1 | BS EN 60034-1 | VDE 0530 | BS 5000 | CAN/CSA-C22.2-100 | NEMA MG1-32.

Low wave distortion:

- THD (100% load) = 2%
- THF < 2%

Complies with: EN61000-6-3, EN61000-6-2 regarding radio interference.

4. Frame Specifications

- Unit mounted on **electro-welded high-resistance steel frame**, painted with epoxy-polyester powder paint. **With retention bath.**
- Connection of the assembly to the frame by means of **anti-vibration dampers.**
- **Fuel tank located on the frame itself.** The engine is equipped with a measuring gauge and fuel system.
- **Tested in a saline mist chamber according to ASTM B-117-09, resistance 500h.**



5. Soundproof canopy Specifications

- Electro-welded **canopy made of high resistance galvanized steel** painted with electrostatic epoxy-polyester powder paint.
- **Interior soundproofing** by means of a lining with soundproofing material.
- **Efficient attenuation silencer -35dB(A)** for the evacuation of gases to the outside with protective cover.
- **Tested in a saline mist chamber according to ASTM B-117-09, resistance 720H. IP44 mechanical protection degree.**



Images for orientation purposes. Dagartech reserves the right to modify the data in this technical sheet without prior notice.

6. Control panel

6.1. Main elements of the control panel

- Protection panel, distribution with **automatic control module** which allows you to work in manual, automatic or signal mode.
- **Emergency stop button.**
- **Protections:**
 - **4-pole magnetothermic protection** against overloads and short circuits.
 - **Protection fuses** for the control set.



6.2. Protection switch

Model **Chint 32A 4P**

6.3. Control module



Model **DSE 3110**

- 1 • Main status and instrument display
- 2 • **Start engine (manual mode)**
- 3 • Automatic mode
- 4 • **Genset stop**
- 5 • Navigation keyboard

Quadro de controlo manual, composto por placa de controlo DSE 3110, que permite o arranque do grupo de forma manual ou mediante controlo remoto através de um sinal externo previamente configurado pelo utilizador.

Todo o módulo é facilmente configurável através de PC, utilizando-se o software específico de configuração DSE.

Dispõe de display iluminado LCD onde se mostram os principais parâmetros do gerador e alertas, 4 saídas e 6 entradas configuráveis, relógios e alarmas programáveis, contahoras.

Diferentes modos de operação: modo MANUAL e modo SINAL.

Outras configurações alternativas estão disponíveis sob pedido, ampliando-se os modos de funcionamento.

Environmental Tests that the module complies with:

BS EN 61000-6-2 (electromagnetic compatibility)
 | BS EN 61000-6-4 (electromagnetic compatibility)
 | BS EN 60950 (electrical safety) | BS EN 61000-6-2 (temperature) | BS EN 60068-2-6 (vibrations)
 | BS EN 60068-2-27 (shock)

6. Control panel

6.3. Control module

(Standard)



(Option)



Model	DSE 3110	DSE 6020 MKII
Operating modes		
STOP mode	✗	✓
MANUAL mode	✓	✓
TEST mode	✗	✓
AUTO mode	✓	✓
Module configuration options		
PC	✓	✓
Group readings		
Generator voltage	✓	✓
Generator current (A)	✗	✓
Generator frequency	✓	✓
Generator load F-N (kW / kVA / kVAr)	✗	✓
Total generator load (kW / kVA / kVAr)	✗	✓
Average generator power factor	✗	✓
Accumulated generator load (kW, kVAh, kWh, kVAh)	✗	✓
Network readings		
Network voltages (ph-N)	✗	✓
Network voltages (ph-ph)	✗	✓
Network frequency	✗	✓
Network current (A)	✗	■
Network load ph-N (kW / kVA / kVAr)	✗	■
Total network load (kW / kVA / kVAr)	✗	■
Engine readings		
Coolant temperature	✗	✓
Oil pressure	✗	✓
Engine fuel level	✗	✓
Engine battery volts	✓	✓
Engine speed	✓	✓
Engine run time	✓	✓

Do you want a superior performance control module?

Contact us and tell us what you need.

Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.

- ✓ Includes
- ✗ Not available
- Optional
- ⓘ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Images for orientation purposes. DagarTech reserves the right to modify the data in this technical sheet without prior notice.

6. Control panel

6.3. Control module

(Standard)



(Option)



Model	DSE 3110	DSE 6020 MKII
Engine protections		
High water temperature	✓	✓
Low oil pressure	✓	✓
Low water level	✓	✓
Fuel reserve by sensor	✗	✓
Second fuel tank control	✗	✓
Shutdown failure	✓	✓
Battery voltage failure	✓	✓
Battery charge alternator failure	✓	✓
Overspeed	✓	✓
Underfrequency	✓	✓
Failure to start	✓	✓
Emergency stop	✓	✓
Maintenance notice	✗	✓
Maintenance Alert	✗	✓
Alternator protections		
High frequency	✓	✓
Low frequency	✓	✓
High voltage	✓	✓
Low voltage	✓	✓
Short circuit	✗	✗
Asymmetry between phases	✗	✗
Incorrect phase sequence	✗	✗
Reverse power	✗	✗
Breaker Trip 4 poles	■	■
Overpressure alarm	✗	✓
Group Signal Drop	✗	✓
Counters		
Hour meter	✓	✓
Kilowatt meter	✗	✓
Starter counter	✗	✓



Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



Do you want a superior performance control module?

Contact us and tell us what you need.



- ✓ Includes
- ✗ Not available
- Optional
- ⓘ Consult

Readings available at control module level.

Confirm the availability of these readings for this generator and engine.

Images for orientation purposes. Dagarotech reserves the right to modify the data in this technical sheet without prior notice.

6. Control panel

6.3. Control module

(Standard)



(Option)



Model	DSE 3110	DSE 6020 MKII
Communications		
RS232	✗	✗
RS485	✗	✗
USB communication port	✓	✓
Modbus IP	✗	■ DSE 855/890/891
Modbus RS 485	✗	■ DSE 855/890/891
PC Software (Mimic)	✗	✓
GSM/GRPS MODEM	✗	■ DSE 890
Remote display < 1km	✗	✗
Remote monitoring	✗	■ DSE 855/890
Input expansion	✗	✗
Output expansion	✗	✗
SNMP protocol	✗	■ DSE 892
Services		
Configurable alarm history	✗	50
External start	✓	✓
Start-up inhibition	■	■
Network Failure Start	✗	✓
Activation of group counter	✗	✓
Activation of grid and group counter	✗	✓
Control of fuel transfer	✗	✓
Motor temperature control	✗	✓
Forced group operation	✗	✓
Free programmable alarms	✓	✓
Group start function in test mode	✗	✓
Free programmable outputs	✓	✓
Multilingual	Symbols	Symbols
Special applications		
GPS localisation	✗	■ DSE 890
Calendar scheduler	✗	✓
DSE configuration suite via PC	✓	✓
Front panel module editing with PIN	✓	✓
Front panel module configuration with PIN	✓	✓
Alternative work	✗	✗
Programmable PLC	✗	✗
Power save mode	✓	✓
Alternative configurations	✓	✓
Dummy load control / load shedding	✗	✗

Do you want a superior performance control module?



Contact us and tell us what you need.



Ask us for further readings in generating sets equipped with electronically managed engines and DSE 7320MKII control module.



- ✓ Includes
- ✗ Not available
- Optional
- ⓘ Consult

Readings available at control module level.

CONFIRM THE AVAILABILITY OF THESE READINGS FOR THIS GENERATOR AND ENGINE.

7. Standard Scope of Delivery



Engine

- **PERKINS 404J-22 Diesel Engine**, 1500 rpm water cooled.
- **Mechanical regulation***.
- **High performance filter** original from the manufacturer.
- **Protection from hot and moving parts.**
- Electric motor starting system, **battery (maintenance-free) with switch** and load alternator driven by **starter motor of 12V**.
- **Efficient high-attenuation exhaust silencer of -30d(BA)** for the evacuation of gases to the outside with protective cover.



Alternator

- **12-Wire, 4-pole brushless STAMFORD S0L2-G alternator** with electronic voltage regulation type AVR (AS540).
- With IP23 protection level.
- **Insulation class H.**
- **Reinforced terminal block** from 60kVA.



Frame

- **Electro-welded frame** made of **high-strength steel**.
- Painted with electrostatic epoxy-polyester powder paint.
- **Anti-vibration dampers** from the engine block to the frame.
- **Fuel tank with capacity of 105 litres with retention bath**, located on the frame itself. Equipped with **cleaning record** to facilitate maintenance work.
- **With measuring gauge** and installation of fuel to the engine.
- **Liquid drainage connection** to the outside.
- **Bedplate tested in a salt spray chamber according to ASTM B-117-09 (500h resistance).**



Soundproofed canopy

- **Electro-welded canopy** of high-strength **galvanized steel**.
- Painted with electrostatic epoxy-polyester powder paint.
- **Interior soundproofing** by means of a **rigid panel made of glass wool with an exterior textile covering**.
- With IP44 mechanical protection level.
- **Cab tested in salt spray chamber according to ASTM B-117-09 (resistance 720h).**



Control panel

- **DeepSea Electronics automatic control module DSE 3110** which allows you to work in manual, automatic or signal mode.
 - It offers multiple event logging and is fully configurable through DeepSea Electronics' free-access specific configuration software.
 - Three-phase network and group detection with measurement for configurations upon network failure.
- **Protections:**
 - 4-pole magnetothermic protection against overloads and short circuits.
 - Protection fuses for the control set.



Other equipment

- **Mechanised fuel nozzle outside with key.**
- **Tropicalised Radiator** for work at 50°C**.
- Prepared for maintenance intervals every 500 hours.
- **Differential protection.**
- **Emergency stop button.**
- **Reinforced pole** centrally-mounted. Central lifting eyebolt from 35kVA.
- **Radiator access door** (in 60 and 100kVA-C models).

*ELECTRONIC MOTOR REGULATION FROM 45 KVA.
**CHECK THE SPECIFICATION ACCORDING TO THE MODEL.



7. Standard Scope of Delivery

The RentalPlus Kit is included in the standard scope of supply of the machine. It consists of the following equipment:

RentalPlus Kit



High performance fuel particle separator filter

- They maximize the separation of residues and particles from the fuel, thus prolonging the service intervals of the group in optimal conditions.



ORIGINAL FROM THE MANUFACTURER



Oil drain pump

- Makes it easy to remove engine oil for an oil change in minutes.



INCLUDED FROM 60KVA.



MX341 and permanent magnet on alternator

- With 2-phase sensing, driven by a permanent magnet generator (PMG), it offers protection against the effects of non-linear loads.



STARTING FROM 100KVA. LOWER MODELS INCLUDE AUXILIARY WINDING.

Power sockets

- Different configurations depending on the model.



	CB 10 20 kVA (PRP)	CB 20 35-45 kVA (PRP)	CB 30 60 kVA (PRP)	CB 40 100-150 kVA (PRP)	CB 50 ≥200 kVA (PRP)
Schuko	1	1	1	2	2
16A 2P+T (230V)			1	1	1
16A 3P+N+T	1				
32A 3P+N+T	1	1	1	2	1
63A 3P+N+T		1	1	1	1
125A 3P+N+T					1

Images for orientation purposes. Dagartech reserves the right to modify the data in this technical sheet without prior notice.


8. Featured options available

Do you need to include some options in the standard equipment of this genset to make it the perfect generator for you? We show you below some of the most demanded options in generator sets of the RentalPlus range.



If your generator set is going to change its location periodically ...

We offer you **construction trailers and approved wheels for road traffic**. And if you still need a more complete solution, we also offer you off-road wheels, with integrated suspensions and more complete equipment.



If noise is a critical factor for you ...

For those applications in which noise is a critical factor, the SuperSilent Kit becomes a highly recommended option, which will offer you sound levels below the market average.

It incorporates an exhaust of -50dB (A) and heavy mass in the alternator. With this Kit, you will reduce the noise levels of the machine between 2 and 3 dB (A).

Check the noise level reduction depending on the model.



Monitor and control your generating set via PC or mobile phone with the DSE 890 module

Including this module, **the device connects to the switchboard server** via ethernet or GPRS (GSM or 3G) connection.

It also includes the GPS function (satellite tracking).

A DSE GSM antenna is required for the correct operation of the DSE890.



Check the availability of these options according to the model and,

if you do not find what you are looking for, please contact us. We have many more options to offer you.

9. Even more options

If you're looking for other features to complete your machine, don't worry.

Below we detail many of the options from the Industrial range that we make available to you to turn your unit into a unique machine.



24 hour tank

AUTONOMY OPTIONS

Increase the autonomy of your generator up to 48 hours, including special tanks

You can choose between **different integrated tanks to increase the autonomy of the unit up to 48 hours** of operation.

You can also incorporate automatic fuel transfer systems for supply from external tanks.

% load	Consumption (l/h)		Capacity (l): 24h tank - N/A l		48h tank - N/A l	
	PRP	ESP	Autonomy (h)		Autonomy (h)	
50%	2,9	-	PRP	ESP	PRP	ESP
75%	4	-	N/A	-	N/A	-
100%	5,5	6,3	N/A	N/A	N/A	N/A



+



Automation kit for network failure operation.

ENGINE - ALTERNATOR OPTIONS

- Electronic engine regulation/management (for models with mechanical regulation)
- 50 / 60Hz selection (only models with electric motor regulation).
- Automation kit for mains failure operation (includes engine heating system + battery charger).
- 6-way fuel valve kit.
- Super Silent kit (includes heavy mass alternator + high attenuation exhaust -50dB(A))
- Alternator anti-condensation resistors.
- Alternator superior impregnation systems.

Images for orientation purposes. DagarTech reserves the right to modify the data in this technical sheet without prior notice.

9. Even more options



Complete stainless steel canopy (304)

MECHANICAL OPTIONS

- Liquid leakage probe (requires retention tray).
- SilentBlocks for levelling.
- Damping - anti-vibration springs.
- Complete stainless steel canopy (304).
- Galvanized frame.
- Non-standard RAL colour.



DSE 2157



DSE 334 network surveillance

COMMUNICATION OPTIONS

- Supplement to the DSE 7320 MKII control board (for models with the DSE 3110 control board in the standard scope of supply).
- DSE 2157 8 potential free output (requires DSE 7320MKII).
- DSE 2130 8 inputs (requires DSE 7320MKII).
- DSE 2548 8 LED diodes (requires DSE 7320MKII).
- GSM modem (RS232) (requires DSE 7320MKII).
- DSE 855.
- DSE 890 webnet.
- DSE 7420 module.
- DSE 334 network surveillance.



Socomec motorised switchboard

POWER OPTIONS

- As an option, you can include a switch cabinet attached to the generating set.
 - Switching with Schneider contactors. 25 to 125 A.
 - Socomec motorised switches: $\geq 125A$.

Images for orientation purposes. Dagartech reserves the right to modify the data in this technical sheet without prior notice.



CHECK THE AVAILABILITY OF THESE OPTIONS DEPENDING ON THE MODEL

¿Necesitas
el plano de instalación
de la versión 24 horas?

Esríbenos
info@dagartech.com

Llámanos
+34 976 141 655

Do you need
the technical drawing
for the 24 hour version?

Write to us at
info@dagartech.com

Call us at
+34 976 141 655

Avez-vous besoin
du plan d'installation
pour la version 24 heures?

Écrivez-nous
info@dagartech.com

Llámanos
+34 976 141 655

Necessita de plano
de instalação em versão
com depósito de 24 horas?

Escreva-nos
info@dagartech.com

Telefone-nos
+34 976 141 655